

Serie Ventilation

Ventilation

Reference : VT730

Ceiling fan 730 M3/h 230V AC IP54



Features

Apto para instalación en exterior: No

Additional features

Relative humidity range (%): 0-95

Electrical connection: Cable

Ventilation

Voltage (V): 230

Voltage (Hz): 50-60

Air flow with filter (m3/h): 730-830

Operating temperature (°C): -30/+80

Service at 40 °C (h): 50

Noise level (dB): 60

Current consumption (A): 0,46-0,51

Energy consumption (W): 98

Static pressure (Pa): 300-440

Overcurrent protection: Térmica

Direction of flow: De dentro hacia fuera

Reversible: No

Bearing: Ball bearing

Heating

Regulating

Technical data

Protection degree: IP54

Materials

Calidad del material: ABS,Iron

Filtro: No

Seal material: Polyurethane

Materiales libres de halógenos: No

Color: Grey RAL 7035

Dimensions

Piece dimensions Height x Width x Depth (mm): 310 x 310 x 140

Cut-off dimensions (mm): Ø220

Certificates and regulations

Directive: 2014/35/EU

Norms: IEC 62208; IEC 61439-1

Packaging

Suministro: Supplied in individual cardboard packaging.

Type d'emballage: BX

U.M. Embalaje - Unitario: C62

Minimum amount of sale: 1

dimensiones_embalaje_unitario_alto_ancho_prof_m: 0.31 x 0.31 x 0.14

Package weight (kg): 5.234

Peso bruto unitario (kg): 5.757

Codes

EAN code GETIM13: 8431044250373

Tariff code: 84145995

ETIM 8.0 Code: EC000320

Código ETIM 9.0: EC000320

Environmental

Fecha verificación sustancias SVHC (reach): 0000-00-00 00:00:00

Packaging: 100% recyclable cardboard

Downloads (Links)

Product drawing STP (URL): <https://ide.es/docs/planos/stp/VT730.stp>

Product drawing DXF (URL): <https://ide.es/docs/planos/dxf/VT730.dxf>

Product drawing (PDF): <https://ide.es/docs/planos/pdf/VT730.pdf>

Assembly instructions: 93062